


01 Chemical Product and Company Identification

Product Name Gamma Stripper
Product Use Floor Stripper
Product Code 3270
For Medical Emergency Call 'Chemtrec' 1-800-424-9300
Supplier's Information Santec Inc.
 1420 East Linden Avenue, Linden NJ 07036

02 Hazards Identification

GHS Classification: 1. Skin - Category 2
 2. Eyes - Category 2A

GHS Label Element: 

Signal Word: Warning
Hazard Statement: May cause skin and eye irritation.
Precautionary Statements: Wear protective gloves, splash goggles, face shield and boots. Wash thoroughly after handling.

Acute Effects
Eyes: Eye irritant. May cause redness or swelling.
Skin: Skin irritant. May cause redness and swelling.
Inhalation: Vapor may be irritating to the nose, throat and lungs.
Ingestion: May be irritating to the mouth, throat and gastrointestinal system. Symptoms may include nausea, vomiting, diarrhea and cramps.

Chronic Effects
Carcinogenicity: No known critical effects or critical hazards.
Product /Ingredient Name: Not available.

03 Composition/ Information on Ingredients

| Name of Hazardous Ingredients | CAS No. | WT.% |
|---------------------------------|-------------|------|
| Monoethanolamine | 141-43-5 | 5-10 |
| Ethylene Glycol Monobutyl Ether | 111-76-2 | 4-8 |
| Nonylphenol Ethoxylate | 127087-87-0 | 2-3 |
| Sodium Hydroxide | 1310-73-2 | 1-3 |

04 First Aid Measures

Eye Contact: Check for and remove any contact lenses. Flush with large quantities of water, holding eyelids open for 15 minutes. Seek medical attention immediately.
Skin Contact: Wash skin with copious amounts of water. If symptoms persist seek medical attention.
Inhalation: Remove to fresh air. Seek medical attention if irritation persists.
Ingestion: Do not induce vomiting. Drink copious amounts of water. Seek medical attention immediately.

05 Fire Fighting Measures

Suitable Fire Extinguishing Media: Use water spray, fog or foam
Specific Hazards Arising from the Chemical: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous Thermal Decomposition Products: Alkaline vapors in a fire.
Specific Fire-Fighting Methods: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Specific Protective Equipment for Fire-Fighters: Fire-Fighters should wear appropriate protective equipment and self contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

06 Accidental Release Measures

Spill Clean Up: Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move Containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

07 Handling and Storage

Handling: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Wash thoroughly after handling.

Storage: Store between the following temperatures: 4.44 to 48.9°C (40 to 120°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

08 Exposure Controls/ Personal Protection

| Ingredient Name | Exposure Limits |
|---------------------------------|--------------------------------|
| Monoethanolamine | OSHA PEL 6 mg/m ³ |
| Ethylene Glycol Monobutyl Ether | OSHA PEL 240 mg/m ³ |
| Sodium Hydroxide | OSHA PEL 0.5 ppm |

Personal Protective Equipment (PPE)

Eyes: Safety glasses, face shield.

Skin: Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Body: For prolonged or repeated handling, use gloves. Nitrile gloves. Rubber gloves. Neoprene gloves.

Respiratory: Use with adequate ventilation. A respirator is not needed under normal and intended conditions of product use.

09 Physical and Chemical Properties

| | |
|---|---|
| Physical State | Clear liquid |
| Color | Water White |
| Odor | Glycol Ether |
| pH | 12.0-12.8 |
| Flash point | > 160°F |
| Explosion limits | Not available |
| Flammability (solid, gas) | Not available |
| Melting point | Not available |
| Boiling point | Not available |
| Evaporation rate (butyl acetate = 1) | Not available |
| Vapor pressure | Not available |
| Vapor density | Not available |
| Relative density | 1.02 (Water = 1) |
| Solubility | Easily soluble in the following materials: cold water and hot water |
| Partition coefficient n-octano/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Odor threshold | Not available |
| Viscosity | Kinematic (room temperature): ≤ 10 cSt (CPS) |

10 Stability and Reactivity

Stability: The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid: No specific data.

Materials to avoid: Strong oxidizers, strong acids.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition should not be produced.



Safety Data Sheet gamma stripper

11 Toxicological Information

| Product /Ingredient Name | Result | Species | Dose |
|---------------------------------|-----------|---------|-------------------|
| Monoethanolamine | LD50 Oral | Rat | 1090 - 3320 mg/kg |
| Ethylene Glycol Monobutyl Ether | LD50 Oral | Rat | 1749 mg/kg |
| Nonylphenol Ethoxylate | LD50 Oral | Rat | 960 - 3980 mg/kg |
| Sodium Hydroxide | LD50 Oral | Rat | 500 mg/kg |

12 Ecological Information

N/A

13 Disposal Considerations

Waste Information
Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

14 Transport Information

| Regulatory Information | UN Number | Proper Shipping Name | Classes | PG* | Label |
|---------------------------|---------------|----------------------|---------|-----|-------|
| DOT Classification | not regulated | - | - | - | - |

Note: DOT classification applies to most package sizes. For specific container size classifications or size exceptions, refer to the bill of lading with your shipment.

PG*: Packing Group

15 Regulatory Information

U.S. Federal Regulations

TSCA 8(b) inventory: All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No listed substance

SARA 302/304 emergency planning and notification: No listed substance

| SARA 313 | Product name | CAS number | Concentration |
|-------------------------------|---------------------|------------|---------------|
| Form R-Reporting requirements | No listed substance | | |

16 Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy of completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of Issue: 06/21/2016

*Hazard Determination System (HDS):

| | |
|--------------|---|
| Health | 2 |
| Reactivity | 0 |
| Flammability | 1 |

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimum hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.